

**PRODUCT DATA SHEET**

# DREXFOIL

**EFFECTIVE ANTI-MOISTURE PROTECTION**

**APPLICATIONS:**

Flooring foils durably insulate concrete flooring against capillary water rising. They exhibit high mechanical, water and water vapour resistance.


**ADVANTAGES:**

- ▶ made from 100 % LDPE polyethylene
- ▶ high mechanical strength
- ▶ appropriate for all types of constructions


**TECHNICAL DATA**

|                       | DL150                | DL200                | DL300                | DL500                |
|-----------------------|----------------------|----------------------|----------------------|----------------------|
| Colour                | black                | black                | black                | black                |
| Thickness             | 150 µm               | 200 µm               | 300 µm               | 500 µm               |
| Elongation at rupture | 150%                 | 170%                 | 260%                 | 380%                 |
| Surface mass          | 138 g/m <sup>2</sup> | 167 g/m <sup>2</sup> | 265 g/m <sup>2</sup> | 443 g/m <sup>2</sup> |
| Breaking strength     | 60 N/5cm             | 70 N/5cm             | 110 N/5cm            | 165 N/5cm            |
| Dimensions            | 6 x 33 m             |                      | 6 x 25 m*            |                      |

\*other dimensions on request


**CHEMICAL RESISTANCE**

It is resistant to chemical substances, fungi, roots (DL500) and bacteria present in the ground. It is completely neutral to the natural environment.



The document is not a contract. Descriptions and technical data are indicative information. We reserve the right to make changes and modifications.


**SYSTEM 2+**
**FPC CERTIFIED**
